

KAM-FCA 602

Foam control additive specifically developed to reduce air entrainment during manufacture and application of water-based paints and adhesives. Universal use. Letdown defoamer with a high persistence. Contains silicone.

Technical Specifications

Composition	:	Emulsion of mineral oil and hydrophobic components. Silicone-containing.
Solid content	:	40%
Viscosity @ 20°C	:	550-750 mPa.s
Specific gravity @ 20°C	:	0.93-0.95 g/cm ³
Appearance	:	White opaque liquid

Applications

KAM-FCA 602 is a slightly viscous, opaque liquid foam control additive designed for universal use in waterborne applications. Its highly concentrated formulation ensures excellent cost efficiency and economical use.

Preferred fields of application:

- Architectural paints
- Water based paints & coatings
- Decorative paints
- Pigment grinding

KAM-FCA 602 may also be used in the production of emulsion binders and in any emulsion adhesive. It features an excellent cost/performance ratio.

KAM-FCA 602 is manufactured using a proprietary production process that ensures excellent storage stability. However, after extended storage periods, slight separation may occur. In such cases, it is recommended to thoroughly shake the product before use.

KAM-FCA 602 can be added prior to processing (Mill-base stage).

Recommended addition level (as supplied): 0.1% to 1.0% based upon on total formulation. When used in water-based and universal colorants, the dosage should be increased to min. 0.8%.

Storage, Safety and Packaging

To be stored in a cool dry place and handled in accordance with good industrial practice. When kept in an original unopened container, it will keep up to min. 1 year from the date of manufacture.